

Portable Electric Power Generator

for ERESKO MF series



Application

The portable electric power generator allows you to use the ERESKO MF units in places, where no power line is available (e.g. at construction building sites).

The generator provides a sinus-shape AC voltage even at full load, at it is absolutely required for operation of this radiating unit.

Features

- Approved for use on construction sites throughout the EU. (Type tested according to regulations 84/532 EEC and 84/536 EEC)

Options

- Set of wheels
- Exhaust pipe



GE imagination at work

Technical Data

Generator	asynchronous
Rated power	3.2 kW
Rated voltage	230 V, 50 Hz, 1~
Rated current	13.9 A
Protection class	IP 23/44
Motor	Honda GX 240
Output	5.8 kW at 3600 min-1
Model	petrol, 4-stroke, air-cooled
Capacity	242 cm ³ , 1 cylinder
Fuel consumption at normal load	1.9 l/h unleaded petrol
Tank size	5.9 l
Starter	Reverser starter (pull starter)
Ignition	electronic, non-contact magnetic ignition
Noise (at $\frac{3}{4}$ rated load)	
Acoustic pressure	72 dB(A) at 10 m metres
Audibility	99 dB(A) / pW(Lwa)
Aggregate	
Dimensions (L x W x H)	775 x 560 x 515 mm (30.5" x 22" x 20.3")
Weight	63 kg (29.5 lbs)
Equipment	automatic oil-level cutout switch 2 PE sockets (16 A), waterproof all-round protective cage



www.gesensinginspection.com

GEIT-30048EN (11/09)

© 2009 General Electric Company. All Rights Reserved. Specifications are subject to change without notice. GE is a registered trademark of General Electric Company. Other company or product names mentioned in this document may be trademarks or registered trademarks of their respective companies, which are not affiliated with GE.

Contact: GE Sensing & Inspection Technologies GmbH, Bogenstrasse 41, 22926 Ahrensburg, Germany, T +49 (0)4102 807 0